

Speedy 100 flexx

Laser engraving system

Mechanics

Working area	610 x 305 mm (24 x 12 inch)
Max. height of work piece	170 mm (6.7 inch) with 1.5 inch lens 157 mm (6.2 inch) with 2.0 inch lens 144 mm (5.7 inch) with 2.5 inch lens 132 mm (5.2 inch) with 2.85 inch lens 125 mm (5.0 inch) with 3.2 inch lens 80 mm (3.2 inch) with 5.0 inch lens
Working table	Ferromagnetic table, honeycomb cutting tabletop
Max. processing speed	2.8 m/s (110 ips)
Acceleration	40 m/s ² (1575 ips ²)
Motors	Brushless DC servo motors
Encoder	Incremental measuring system
Optical elements	Telescope, lens and mirrors
Lens	2.85 inch (flexx); 1.5 inch, 2.0 inch, 2.5 inch (CO ₂); 3.2 inch, 5.0 inch (fiber)
Accuracy	+/- 0.015 mm (0.0006 inch), over the whole working area
Addressable accuracy	5 µm (0.0002 inch)
Accuracy to size of parts	According to material and process
Maximum material load	10 kg (22 lbs), load over the whole working area
Interface	USB

Features standard

Lens	2.85 inch
InPack Technology™	Protects working head and all moving parts from dust
Exhaust	For entire working area
Software	Ruby®
Operating console	Keypad, safety-switch, system turnkey; PC and Monitor not included
Laser Pointer	655 nm, <0,99 mWcw
Autofocus	Light bar sensor and software

Work area light

LED

Options

Temperature sensor

To check temperature inside the work area.

Accessories

JobControl® CUT

Software to manipulate and optimize cut geometries
– to be used with JobControl® Expert only (separate license)

UniDrive

Supports different operating systems e.g. iOS, or multiple design stations

Rotary attachment

Available with conus, three-jaw chuck, three-jaw ring chuck or Drill chuck

Trolley

Trolley with storage shelf

TroCare

Comprehensive package of technical services

Laser

Laser system CO₂

Sealed-off laser, maintenance free, air cooled, wavelength 10.6 µm

Laser power CO₂

60 W

Laser system fiber

maintenance free, air cooled, wavelength 1064 nm

Laser power fiber

20 and 30 W

Dimensions & weight

Width x Depth x Height

1018 x 784 x 1004 mm (40 x 30.9 x 39.5 inch)

Weight

Approx. 150 kg / 330 lbs (depending on laser power)

Safety & environment

Laser class

CDRH laser class 2

Interlock

Double Interlock safety system

Ambient conditions

Mandatory ambient temperature +15° to +25° C or 59° to 77° F
Humidity 40% to max. 70%, not condensing
Dust free environment (2nd degree according to IEC 60947-1)

Certificates

CE compliant, FDA listed

Exhaust

Exhaust working point

Min. 200 m³/h at 1.000 Pa (Min. 117.7 cfm at 4.015 in H₂O)

Cooling

Air cooling	Active air flow cooling with fan
-------------	----------------------------------

Electrical

Voltage & power consumption	1 ~ AC 110-230V 50/60Hz, 1.3 kW (60 W)
-----------------------------	--

Subject to change without notice.

Errors and omissions excepted.

Model identification Speedy 100X-8063

September 2020 – Update July 2020